

uum Truck 2 Axle

STANDARD FEATURES INCLUDE:

4 x 2 Regular Cab.

GVRW 19,500 lbs.

500 Gallon carbon steel. 3/16" carbon steel, 100% dish

Carbon steel T-Bar. MOUNTING: WM HD spring mounting 20" Full opening, carbon steel MANHOLE: **RELIEF VALVE:** Brass vacuum relief, adjustable.

OUTLET: 4" out rear of tank **VALVING:** 4" Bronze lever

4" Aluminum Male Camlock CONNECTION: PRIMARY DOME: 20" carbon steel full opening MOISTURE TRAP: 3" Secondary scrubber

PRIMARY SHUTOFF: Stainless steel ball float stopper

GAUGES: Two (2) each

VACUUM PUMP: 400 CFM water cooled, vacuum/pressure,

hydraulic driven

MUFFLER: 3" Oil catch with drain valve WET KIT: "HOT SHIFT" PTO, hydraulic pump **BUMPER:** Carbon steel fabricated at rear **HOSE TRAYS:** Full length incorporated to act as fenders.

LIGHTING: L.E.D. per D.O.T. PAINT: **Acrylic Urethane**

MANY OPTIONS AVAILABLE, INCLUDING:

4x2 and 4x4 Chassis

Standard, Extended or Crew Cab 19,500-41,000 GVW Chassis 500 Gal - 2000 Gal Debris Tanks

Barrel- Carbon, Aluminum and Stainless Heads- Carbon, Aluminum and Stainless

Rear Opening Head

Hydraulic Dump packages Various Mounting packages Multiple Manholes and locations Multiple Relief valves and settings

Various Outlet options Connections for 2" up to 6" 400 CFM up to 1000 CFM

Hydraulically driven or Direct Driven units

Wash down pump

Water tank

Various Bumper configurations Various Fender configurations

Hose Tubes and various other hose storage configurations

Suction Boom



800-692-5844 P.O. Box 100 2704 Railroad Ave. 209-537-4747 Ceres CA. 95307 (Fax) 209-537-1753